



Solid Gel



Electrodes / Pouch  
Electrodes / Case

## APPLICATION

For: Hours

## PRODUCT INFORMATION

Shape  
Size (excl. grip)  
Sensor (Eyelet) Diameter  
Substrate Thickness (adapter excluded)  
Total Product Surface Area  
Gel Area  
Adhesive Area  
Integrated Lead Wire (length / color)

## MATERIALS

Substrate Material  
Adhesive  
Gel Type  
Foam (Sponge) Material  
Release Liner  
Sensor Polymer  
Adaptor / Connector (Stud)  
Integrated Lead Wire Jacketing  
Integrated Lead Wire Cord

## ELECTRICAL PERFORMANCE (ANSI/AAMI EC 12)

|  |        |
|--|--------|
| <b>ACZ impedance</b> (before defib simulation) @10 Hz              | Ohm    |
| <b>DC Offset Voltage</b> (before defib simulation)                 | mV     |
| <b>SDR Slope</b> (remaining potential after defib) @ 30 Sec int.   | mV/sec |
| <b>ACZ impedance repeat</b> (after defib simulation)               | Ohm    |
| <b>COIIN</b> (combined offset instability and inner noise)         | µV     |
| <b>Bias Current Tolerance</b> (DC offset voltage after DC loading) | mV     |

## FEATURES

MR Conditional  
X-ray Translucence  
Integrated Abrader  
Repositionability

## PACKAGING

|   |          |
|---|----------|
| <b>Product Packaging Material</b>           |          |
| <b>Resealable Pouch</b>                     |          |
| <b>Product Packaging Size (L x W)</b>       | in<br>cm |
| <b>Department Packaging - Box (L x W)</b>   | in<br>cm |
| <b>Transport Packaging - Carton (L x W)</b> | in<br>cm |

## BIOCOMPATIBILITY

ISO 10993  
Latex Free

## ENVIRONMENTAL

Halogenated Hydrocarbon Content (e.g. PVC)  
Phthalate Derivatives Content (e.g. DEHP)  
RoHS Compliant  
REACH Compliant

## SHELF LIFE

**Product Shelf Life** (in accordance with storage guidelines)

## REGULATORY STATUS

**Reorder Part Number:**