



Solid Gel

Electrodes / Pouch
Electrodes / Case

APPLICATION

For: Hours

PRODUCT INFORMATION

- Shape
- Size (excl. grip)
- Sensor (Eyelet) Diameter
- Substrate Thickness (adapter excluded)
- Total Product Surface Area
- Gel Area
- Adhesive Area
- Integrated Lead Wire (length / color)

MATERIALS

- Substrate Material
- Adhesive
- Gel Type
- Foam (Sponge) Material
- Release Liner
- Sensor Polymer
- Adaptor / Connector (Stud)
- Integrated Lead Wire Jacketing
- Integrated Lead Wire Cord

ELECTRICAL PERFORMANCE
(ANSI/AAMI EC 12)

ACZ impedance (before defib simulation) @10 Hz	Ohm
DC Offset Voltage (before defib simulation)	mV
SDR Slope (remaining potential after defib) @ 30 Sec int.	mV/sec
ACZ impedance repeat (after defib simulation)	Ohm
COIIN (combined offset instability and inner noise)	µV
Bias Current Tolerance (DC offset voltage after DC loading)	mV

FEATURES

- MR Conditional
- X-ray Translucence
- Integrated Abrader
- Repositionability

PACKAGING

Product Packaging Material	
Resealable Pouch	
Product Packaging Size (L x W)	in cm
Department Packaging - Box (L x W)	in cm
Transport Packaging - Carton (L x W)	in cm

BIOCOMPATIBILITY

- ISO 10993
- Latex Free

ENVIRONMENTAL

- Halogenated Hydrocarbon Content (e.g. PVC)
- Phthalate Derivatives Content (e.g. DEHP)
- RoHS Compliant
- REACH Compliant

SHELF LIFE

Product Shelf Life (in accordance with storage guidelines)

REGULATORY STATUS

Reorder Part Number: